# LW 320 B AL Nautic



The LW 320 B Al Nautic is designed for mobile use but also suitable for stationary applications. It can optionally be used as a fully automatic stationary system by adding the available extras. It comes ready to start with 4 stroke Briggs & Stratton motor and with a lightweight and seawater resistant aluminum frame.

### **Specifications**

- » 4 stroke Briggs & Stratton drive motor
- » Seawater resistant aluminum-frame (Colour: RAL 9006)
- » Crash frame c/w 4 carrying handles and sling eyes
- » Hour counter and integrated pressure gauge
- » Manual condensate drain
- » 4x Filling hose c/w filling valve
- » Pressure maintaining and non return valve
- » All pistons with steel piston rings
- » **NEW** Improved lubrication system with adjustable oil pump
- » Low pressure oil pump with oil sieve
- » Oil- / Water separators in stainless steel
- » Safety valves after each stage
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice (DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification an accordance to EN 12021

#### **Options**

- » Automatic condensate drain
- » Automatic stop at final pressure
- » 200 and 300 bar parallel filling pressures
- » Additional high pressure outlet
- » Oil pressure gauge
- » Wheel set



## Technical Data

1111 000 B 41 41 41	
LW 320 B AL Nautic	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm³/h] / [cfm]:	320 / 19.2 / 11.3
Max. Pressure [bar]:	350
RPM [1/min]:	1500
No of cylinders / No of stages:	3/3
Prime mover type:	4 stroke gasoline engine
Drive power [kW]:	9.7
Cooling air requirement [Nm3/h]:	2460
Lubrication type:	Oil pump + Splash oil
Oil capacity [litre]:	1.8
Oil pressure [bar]:	1.8 (+/- 0.3)
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m³ at +20°C] 1):	750 (at +20°C / approx. 39 h)
Dimensions W x D x H [mm]:	1290 x 640 x 740
Weight [kg]:	167
Noise level (measured at 1 m) [dB(A)]:	95 (measured at 1 m)

<sup>1)</sup> In accordance with EN 12021

#### **Lenhardt & Wagner GmbH**

An der Tuchbleiche 39 68623 Hüttenfeld / Germany

Phone: +49 (0)62 56 - 8 58 80 -0 Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com Internet: www. lw-compressors.com